



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED





2	4	6
V_AP	CAN_L	Reserved
1	3	5
GND	CAN_H	Reserved

A-A
5:1



Technical information:

1. Designed for aircraft less than 50kg;
2. Beam width: 160°;
3. Operating temperature: from -40 to +60°C;
4. Power supply: from 5 to 24VDC;
5. Power consumption max: 0.2W/6VDC;

This drawing and any information or descriptive material set out on it are the confidential and copyright property of UAVOS ® and MUST NOT BE DISCLOSED, COPIED, LOANED in whole or part or used for any purpose without the written permission of UAVOS .			UNLESS OTHERWISE SPECIFIED DIM ARE IN MILLIMETERS [DIM ARE IN INCHES] TOL ON ANGLES $\pm 0.5^\circ$ 0 PLACE ± 0.5 1 PLACE ± 0.1 INTERPRET DIM AND TOL PER ASME Y14.5M Surface Finish: Ra3.2	DRAFTER			 UAVOS TITLE	GPS receiver mini
				CHECKER				
				DEV ENGR				
				CONTRACT NO.	UAVOS FUNDED			
				THIRD ANGLE PROJECTION	MATERIAL			
								
NEXT ASSY	USED ON							
APPLICATION								

SIZE	CAGE CODE	DRAWING NUMBER	REV
A2		UV01.431329.102.365	10
SCALE	2:1	WEIGHT KG	0.049
SHEET		1 OF 1	