REVISIONS			
REV	DESCRIPTION	DATE	APPROVED



Harwin M80-9420605 plug



2	4	6
V_AP	CAN_L	Reseved
1	3	5
GND	CAN_H	Reseved



A-A
5 : 1





Technical information:
1. Designed for aircraft less than 50kg;
2. Beam width: 160°;
3. Operating temperature: from -40 to+60°C;
4. Power supply: from 5 to 24VDC;
5. Power consumption max: 0.2W/6VDC;

This drawing and any information or descriptive material set out on it are the confidential and copyright property of **UAVOS ©** and MUST NOT BE DISCLOSED, COPIED, LOANED in whole or part or used for any purpose without the written permission of **UAVOS**.

NEXT ASSY | USED ON

APPLICATION

UNLESS OTHERWISE SPECIFIED
DIM ARE IN MILLIMETERS
[DIM ARE IN INCHES]
TOL ON ANGLES **±0.5°**
0 PLACE **±0.5** 1 PLACE **±0.1**
INTERPRET DIM AND TOL
PER **ASME Y14.5M**
Surface Finish: **Ra3.2**

THIRD ANGLE PROJECTION

DRAFTER
CHECKER
DEV ENGR

CONTRACT NO.
UAVOS FUNDED

MATERIAL

UAVOS

UAVOS

TITLE

GPS receiver mini

SIZE	CAGE CODE	DRAWING NUMBER	REV
A2		UV01.431329.102.365	10

SCALE 2:1 | WEIGHT KG 0.049 | SHEET 1 OF 1