




Harwin M300-3240696M1 plug



2	4	6
GND	CAN_H	reserved
1	3	5
reserved	V_AP	CAN_L



Technical information:  
1. Designed for aircraft less than 50kg;  
2. Operating temperature: from -40 to +60°C;  
3. Power supply: 12VDC;

This drawing and any information or descriptive material set out on it are the confidential and copyright property of UAVOS © and MUST NOT BE DISCLOSED, COPIED, LOANED in whole or part or used for any purpose without the written permission of UAVOS.

NEXT ASSY	USED ON
APPLICATION	

UNLESS OTHERWISE SPECIFIED  
DIM ARE IN MILLIMETERS  
[DIM ARE IN INCHES]  
TOL ON ANGLES  $\pm 0.5^\circ$   
0 PLACE  $\pm 0.5$  1 PLACE  $\pm 0.1$   
INTERPRET DIM AND TOL  
PER ASME Y14.5M  
Surface Finish: **Ra3.2**

THIRD ANGLE PROJECTION

DRAFTER		
CHECKER		
DEV ENGR		
CONTRACT NO.		
UAVOS FUNDED		
MATERIAL		

**UAVOS**

**Data Processing Unit Of Pitot Tube  
Micro (DPU-PTM)**

SIZE <b>A2</b>	CAGE CODE	DRAWING NUMBER <b>UV01.431329.103.320</b>	REV <b>10</b>
SCALE <b>2:1</b>	WEIGHT KG <b>0.018</b>	SHEET <b>1 OF 1</b>	